

What is claimed is:

1 (currently amended). A **shower support comprising for**
 2 a shower head **and a hose, comprising:**
 3 a mounting fixture for mounting the support such that the support is
 4 adjustable,
 5 **on a pivotable** arm jutting out of the mounting fixture, **said arm having**
 6 **a first end connected to the mounting fixture and a second opposite end,**
 7 **with a water conduit extending from the mounting fixture to at least one**
 8 **additional shower fixture attached along said arm,**
 9 a receptacle **adapted to receive for a the** shower head **when the**
 10 **shower head is not in hand operation, said receptacle being** arranged in
 11 the vicinity of a for **at said second opposite** end of the arm away from the
 12 mounting fixture, **which wherein the shower head and the** receptacle **is are**
 13 configured **such that the to allow the** shower head **is detachable to be**
 14 **removed from the receptacle during hand operation of the shower head**
 15 **on the hose from said receptacle,** and
 16 **at least one additional shower fixture attached to the arm,**
 17 wherein the shower head is supplied with water by **the a** hose and
 18 wherein the additional shower fixture is arranged to be supplied with water **by**
 19 **the water conduit** independently of the shower head.

Claim 2 is canceled.

1 3(currently amended). The shower support according to claim 1,
 2 wherein **the water conduit is defined by** a channel **that** extends through the
 3 arm and leads to the additional shower fixture.

1 4(previously presented). The shower support according to claim 1,
 2 wherein the arm comprises a length of hollow, profiled stock, at least from the
 3 mounting fixture to the additional shower fixture.

1 5(previously presented). The shower support according to claim 1,
2 wherein the additional shower fixture is arranged between the mounting fixture
3 and the far end of the arm.

1 6(previously presented). The shower support according to claim 1,
2 wherein a direction of a jet exiting the additional shower fixture is adjustable.

1 7(previously presented). The shower support according to claim 1,
2 wherein the additional shower fixture is mounted on a side of the arm jutting
3 from the mounting fixture.

1 8(previously presented). The shower support according to claim 1,
2 wherein at least one said additional shower fixture is mounted on a underside
3 of the arm jutting from the mounting fixture.

1 9(currently amended). The shower support according to claim 1,
2 having ~~several~~ **multiple said** additional ~~said~~ shower fixtures and ~~a water-~~
3 **wherein the water conduit provides a water** supply ~~conduit~~ common to all
4 the additional shower fixtures.

1 10(previously presented). The shower support according to claim 1,
2 wherein the additional shower fixture is nondetachable.

Claim 11 was canceled.

1 12(previously presented). The shower support according to claim 1,
2 wherein the arm is pivotable relative to the mounting fixture about a horizontal
3 axis orthogonal to a longitudinal axis of the arm.

4 13(previously presented). The shower support according to claim 12,
 5 wherein a water conduit passes a pivotable connection of the arm to the
 6 mounting fixture.

1 14(previously presented). The shower support according to claim 1,
 2 wherein the arm is configured in the form of a fork.

1 15(previously presented). The shower support according to claim 14,
 2 wherein the additional shower fixtures are arranged on outer faces of tines of
 3 the fork.

Claims 16 and 17 were canceled.